

DECLARATION OF PERFORMANCE No 2527 -1-7-2014

- 1.
 Unique identification code of the product-type:
 2TTPK
 Joya Tunnel PL full circulation

 slow heat release appliance fired by solid fuel
 5000 fuel
 5000 fuel
 5000 fuel
- 2. Intended use: Space heating in residential buildings
- 3. Manufacturer: NunnaUuni Oy, Joensuuntie 1344 C, 83940 Nunnanlahti, www.nunnauuni.com
- 5. System of AVCP: AVCP 3
- 6a. Harmonised standard: EN 15250:2007. The notified institution Ramboll Analytics (no. 2415) performed the initial testing under system 3 and issued the test reports.

7. Declared performances:

Harmonized technical specification	EN 15250:2007
Essential characteristics	Performance
Fire safety	
- Reaction to fire	-A1
- Distance to adjacent combustible material	- Minimum distances
	Behind: 1000 mm
	Sidewards: 150 mm
	In front: 1000 mm
	Ceiling: 200 mm
 Release of dangerous substance 	- Pass
Emission of combustion products	CO 0,09 %
Surface temperature	Pass
Electrical safety	Pass
Cleanability	Pass
Flue gas temperature	258 ºC
Mechanical resistance (to carry a chimney/flue)	Pass
Energy efficiency	78 %
Thermal energy	54,1 kWh
	100 % 6,2 h
	50 % 20,6 h
	25 % 33,3 h
Fuel type	Wood logs
Max amount of wood	4 x 4 = 16 kg

Follow the user's instruction.

- 8.
- The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Nunnanlahti 28.3.2018

Tuomo Järvinen Managing director